

Bulgarian Module for datetime2 Package

Nicola L. C. Talbot (inactive)

2018-03-19 (v1.1)

This module is currently unmaintained and may be subject to change. If you want to volunteer to take over maintenance, contact me at <http://www.dickimaw-books.com/contact.html>

Abstract

This is the Bulgarian language module for the `datetime2` package. If you want to use the settings in this module you must install it in addition to installing `datetime2`. If you use `babel` or `polyglossia`, you will need this module to prevent them from redefining `\today`. The `datetime2 useregional` setting must be set to `text` or `numeric` for the language styles to be set. Alternatively, you can set the style in the document using `\DTMsetstyle`, but this may be changed by `\date<language>` depending on the value of the `useregional` setting.

I've copied the date style from `babel-bulgarian's \today`.

I don't know if these settings are correct as I can't speak Bulgarian. In particular, I don't know if the `bulgarian` time style is correct. Currently this just uses the `default` time style. Please be aware that this may change. Whoever takes over maintenance of this module may can change it as appropriate.

The new maintainer should add the line:

The Current Maintainer of this work is Name.

to the preamble part in `datetime2-bulgarian.ins` where Name is the name of the maintainer(s) and replace the 'inactive' status to 'maintained'.

Currently there is only a regionless style.

1 The Code

1.1 UTF-8

This file contains the settings that use UTF-8 characters. This file is loaded if XeLaTeX or LuaLaTeX are used. Please make sure your text editor is set to UTF-8 if you want to view this code. Identify module

```
1 \ProvidesDateTimeModule{bulgarian-utf8}[2018/03/19 v1.1]
```

\DTMbulgarianordinal

```
2 \newcommand*{\DTMbulgarianordinal}[1]{%
3   \number#1
4 }
```

\DTMbulgarianyear

```
5 \newcommand*{\DTMbulgarianyear}[1]{%
6   \number#1
7   \DTMtexorpdfstring{\protect~}{\space}г.%
8 }
```

\DTMbulgarianmonthname Bulgarian month names.

```
9 \newcommand*{\DTMbulgarianmonthname}[1]{%
10  \ifcase#1
11  \or
12  януари%
13  \or
14  февруари%
15  \or
16  март%
17  \or
18  април%
19  \or
20  май%
21  \or
22  юни%
23  \or
24  юли%
25  \or
26  август%
27  \or
28  септември%
29  \or
30  октомври%
31  \or
32  ноември%
33  \or
34  декември%
35  \fi
36 }
```

\DTMbulgarianMonthname As above but capitalize.

```
37 \newcommand*{\DTMbulgarianMonthname}[1]{%
38  \ifcase#1
39  \or
40  Януари%
41  \or
42  Февруари%
43  \or
```

```

44 Март%
45 \or
46 Апрель%
47 \or
48 Май%
49 \or
50 Юни%
51 \or
52 Юли%
53 \or
54 Август%
55 \or
56 Септември%
57 \or
58 Октомври%
59 \or
60 Ноември%
61 \or
62 Декември%
63 \fi
64 }

```

If abbreviated dates are supported, short month names should be likewise provided.

1.2 ASCII

This file contains the settings that use \LaTeX commands for non-ASCII characters. This should be input if neither Xe \LaTeX nor Lua \LaTeX are used. Even if the user has loaded `inputenc` with `utf8`, this file should still be used not the `datetime2-bulgarian-utf8.ldf` file as the non-ASCII characters are made active in that situation and would need protecting against expansion. Identify module

```
65 \ProvidesDateTimeModule{bulgarian-ascii}[2018/03/19 v1.1]
```

If abbreviated dates are supported, short month names should be likewise provided.

```
\DTMbulgarianordinal
```

```

66 \newcommand*{\DTMbulgarianordinal}[1]{%
67   \number#1
68 }

```

```
\DTMbulgarianyear
```

```

69 \newcommand*{\DTMbulgarianyear}[1]{%
70   \number#1
71   \DTMtexpdfstring{\protect~}{\space}\protect\cyrg.%
72 }

```

```

\DTMbulgarianmonthname Bulgarian month names.
73 \newcommand*{\DTMbulgarianmonthname}[1]{%
74 \ifcase#1
75 \or
76 \protect\cyrya\protect\cyrn\protect\cyru\protect\cyra\protect\cyrr
77 \protect\cyri
78 \or
79 \protect\cyrf\protect\cyre\protect\cyrv\protect\cyrr\protect\cyru
80 \protect\cyra\protect\cyrr\protect\cyri
81 \or
82 \protect\cyrm\protect\cyra\protect\cyrr\protect\cyrt
83 \or
84 \protect\cyra\protect\cyrp\protect\cyrr\protect\cyri\protect\cyr1
85 \or
86 \protect\cyrm\protect\cyra\protect\cyrishrt
87 \or
88 \protect\cyryu\protect\cyrn\protect\cyri
89 \or
90 \protect\cyryu\protect\cyr1\protect\cyri
91 \or
92 \protect\cyra\protect\cyrv\protect\cyrg\protect\cyru\protect\cyrS
93 \protect\cyrt
94 \or
95 \protect\cyrS\protect\cyre\protect\cyrp\protect\cyrt\protect\cyre
96 \protect\cyrm\protect\cyrv\protect\cyrr\protect\cyri
97 \or
98 \protect\cyro\protect\cyrk\protect\cyrt\protect\cyro\protect\cyrm
99 \protect\cyrv\protect\cyrr\protect\cyri
100 \or
101 \protect\cyrn\protect\cyro\protect\cyre\protect\cyrm\protect\cyrv
102 \protect\cyrr\protect\cyri
103 \or
104 \protect\cyrd\protect\cyre\protect\cyrk\protect\cyre\protect\cyrm
105 \protect\cyrv\protect\cyrr\protect\cyri
106 \fi
107 }

```

```

\DTMbulgarianMonthname As above but start with a capital.
108 \newcommand*{\DTMbulgarianMonthname}[1]{%
109 \ifcase#1
110 \or
111 \protect\CYRYA\protect\cyrn\protect\cyru\protect\cyra\protect\cyrr
112 \protect\cyri
113 \or
114 \protect\CYRF\protect\cyre\protect\cyrv\protect\cyrr\protect\cyru
115 \protect\cyra\protect\cyrr\protect\cyri
116 \or
117 \protect\CYRM\protect\cyra\protect\cyrr\protect\cyrt
118 \or
119 \protect\CYRA\protect\cyrp\protect\cyrr\protect\cyri\protect\cyr1

```

```

120 \or
121 \protect\CYRM\protect\cyra\protect\cyrishrt
122 \or
123 \protect\CYRYU\protect\cyrn\protect\cyrj
124 \or
125 \protect\CYRYU\protect\cyr1\protect\cyrj
126 \or
127 \protect\CYRA\protect\cyrv\protect\cyrq\protect\cyru\protect\cyrp
128 \protect\cyrp
129 \or
130 \protect\CYRS\protect\cyrq\protect\cyrp\protect\cyrp\protect\cyrq
131 \protect\cyrp\protect\cyrv\protect\cyrp\protect\cyrj
132 \or
133 \protect\CYRO\protect\cyrk\protect\cyrp\protect\cyrq\protect\cyrp
134 \protect\cyrv\protect\cyrp\protect\cyrj
135 \or
136 \protect\CYRN\protect\cyrq\protect\cyrq\protect\cyrp\protect\cyrv
137 \protect\cyrp\protect\cyrj
138 \or
139 \protect\CYRD\protect\cyrq\protect\cyrk\protect\cyrq\protect\cyrp
140 \protect\cyrv\protect\cyrp\protect\cyrj
141 \fi
142 }

```

1.3 Main Bulgarian Module (**datetime2-bulgarian.1df**)

Identify Module

```

143 \ProvidesDateTimeModule{bulgarian}[2018/03/19 v1.1]
    Need to find out if XeTeX or LuaTeX are being used.
144 \RequirePackage{ifxetex,ifluatex}
    XeTeX and LuaTeX natively support UTF-8, so load bulgarian-utf8 if either
    of those engines are used otherwise load bulgarian-ascii.
145 \ifxetex
146 \RequireDateTimeModule{bulgarian-utf8}
147 \else
148 \ifluatex
149 \RequireDateTimeModule{bulgarian-utf8}
150 \else
151 \RequireDateTimeModule{bulgarian-ascii}
152 \fi
153 \fi

```

Define the **bulgarian** style. The time style is the same as the **default** style provided by **datetime2**. This may need correcting. For example, if a 12 hour style similar to the **englishampm** (from the **english-base** module) is required.

Allow the user a way of configuring the **bulgarian** and **bulgarian-numeric** styles. This doesn't use the package wide separators such as `\dtm@datetimesep` in case other date formats are also required.

`\DTMbulgariandaymonthsep` The separator between the day and month for the text format.
154 `\newcommand*{\DTMbulgariandaymonthsep}{\space}`

`\DTMbulgarianmonthyearsep` The separator between the month and year for the text format.
155 `\newcommand*{\DTMbulgarianmonthyearsep}{\space}`

`\DTMbulgariandatetimesep` The separator between the date and time blocks in the full format (either text or numeric).
156 `\newcommand*{\DTMbulgariandatetimesep}{\space}`

`\DTMbulgariantimezonesep` The separator between the time and zone blocks in the full format (either text or numeric).
157 `\newcommand*{\DTMbulgariantimezonesep}{\space}`

`\DTMbulgariandatesep` The separator for the numeric date format.
158 `\newcommand*{\DTMbulgariandatesep}{.}`

`\DTMbulgariantimesep` The separator for the numeric time format.
159 `\newcommand*{\DTMbulgariantimesep}{:}`

Provide keys that can be used in `\DTMlangsetup` to set these separators.

```

160 \DTMdefkey{bulgarian}{daymonthsep}{\renewcommand*{\DTMbulgariandaymonthsep}{#1}}
161 \DTMdefkey{bulgarian}{monthyearsep}{\renewcommand*{\DTMbulgarianmonthyearsep}{#1}}
162 \DTMdefkey{bulgarian}{datetimesep}{\renewcommand*{\DTMbulgariandatetimesep}{#1}}
163 \DTMdefkey{bulgarian}{timezonesep}{\renewcommand*{\DTMbulgariantimezonesep}{#1}}
164 \DTMdefkey{bulgarian}{datesep}{\renewcommand*{\DTMbulgariandatesep}{#1}}
165 \DTMdefkey{bulgarian}{timesep}{\renewcommand*{\DTMbulgariantimesep}{#1}}

```

TODO: provide a boolean key to switch between full and abbreviated formats if appropriate. (I don't know how the date should be abbreviated.)

Define a boolean key that determines if the time zone mappings should be used.

```

166 \DTMdefboolkey{bulgarian}{mapzone}[true]{}

```

The default is to use mappings.

```

167 \DTMsetbool{bulgarian}{mapzone}{true}

```

Define a boolean key that determines if the day of month should be displayed.

```

168 \DTMdefboolkey{bulgarian}{showdayofmonth}[true]{}

```

The default is to show the day of month.

```

169 \DTMsetbool{bulgarian}{showdayofmonth}{true}

```

Define a boolean key that determines if the year should be displayed.

```

170 \DTMdefboolkey{bulgarian}{showyear}[true]{}

```

The default is to show the year.

```

171 \DTMsetbool{bulgarian}{showyear}{true}

```

Define the `bulgarian` style. (TODO: implement day of week?)

```
172 \DTMnewstyle
173 {bulgarian}% label
174 {% date style
175   \renewcommand*\DTMdisplaydate[4]{%
176     \DTMifbool{bulgarian}{showdayofmonth}
177     {\DTMbulgarianordinal{##3}\DTMbulgariandaymonthsep}%
178     }%
179     \DTMbulgarianmonthname{##2}%
180     \DTMifbool{bulgarian}{showyear}%
181     {%
182       \DTMbulgarianmonthyearsep
183       \DTMbulgarianyear{##1}%
184     }%
185   }%
186 }%
187 \renewcommand*\DTMdisplaydate[4]{%
188   \DTMifbool{bulgarian}{showdayofmonth}
189   {%
190     \DTMbulgarianordinal{##3}\DTMbulgariandaymonthsep
191     \DTMbulgarianmonthname{##2}%
192   }%
193   {%
194     \DTMbulgarianMonthname{##2}%
195   }%
196   \DTMifbool{bulgarian}{showyear}%
197   {%
198     \DTMbulgarianmonthyearsep
199     \DTMbulgarianyear{##1}%
200   }%
201   }%
202 }%
203 }%
204 {% time style (use default)
205   \DTMsettimestyle{default}%
206 }%
207 {% zone style
208   \DTMresetzones
209   \DTMbulgarianzonemaps
210   \renewcommand*\DTMdisplayzone[2]{%
211     \DTMifbool{bulgarian}{mapzone}%
212     {\DTMusedzonemapordefault{##1}{##2}}%
213     {%
214       \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
215       \ifDTMshowzoneminutes\DTMbulgariantimesep\DTMtwodigits{##2}\fi
216     }%
217   }%
218 }%
219 {% full style
```

```

220 \renewcommand*\DTMdisplay}[9]{%
221 \ifDTMshowdate
222 \DTMdisplaydate{##1}{##2}{##3}{##4}%
223 \DTMbulgariandatatetimesep
224 \fi
225 \DTMdisplaytime{##5}{##6}{##7}%
226 \ifDTMshowzone
227 \DTMbulgariantimezonesep
228 \DTMdisplayzone{##8}{##9}%
229 \fi
230 }%
231 \renewcommand*\DTMDisplay}[9]{%
232 \ifDTMshowdate
233 \DTMDisplaydate{##1}{##2}{##3}{##4}%
234 \DTMbulgariandatatetimesep
235 \fi
236 \DTMDisplaytime{##5}{##6}{##7}%
237 \ifDTMshowzone
238 \DTMbulgariantimezonesep
239 \DTMDisplayzone{##8}{##9}%
240 \fi
241 }%
242 }%

Define numeric style.
243 \DTMnewstyle
244 {bulgarian-numeric}% label
245 {% date style
246 \renewcommand*\DTMdisplaydate[4]{%
247 \DTMifbool{bulgarian}{showdayofmonth}%
248 {%
249 \number##3 % space intended
250 \DTMbulgariandatesep
251 }%
252 }%
253 \number##2 % space intended
254 \DTMifbool{bulgarian}{showyear}%
255 {%
256 \DTMbulgariandatesep
257 \number##1 % space intended
258 }%
259 }%
260 }%
261 \renewcommand*\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
262 }%
263 {% time style
264 \renewcommand*\DTMdisplaytime[3]{%
265 \number##1
266 \DTMbulgariantimesep\DTMtwodigits{##2}%
267 \ifDTMshowseconds\DTMbulgariantimesep\DTMtwodigits{##3}\fi

```



```

268   }%
269 }%
270 {% zone style
271   \DTMresetzones
272   \DTMbulgarianzonemaps
273   \renewcommand*{\DTMdisplayzone}[2]{%
274     \DTMifbool{bulgarian}{mapzone}%
275     {\DTMusezonemapordefault{##1}{##2}}%
276     {%
277       \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
278       \ifDTMshowzoneminutes\DTMbulgariantimesep\DTMtwodigits{##2}\fi
279     }%
280   }%
281 }%
282 {% full style
283   \renewcommand*{\DTMdisplay}[9]{%
284     \ifDTMshowdate
285       \DTMdisplaydate{##1}{##2}{##3}{##4}%
286       \DTMbulgariandatatetimesep
287     \fi
288     \DTMdisplaytime{##5}{##6}{##7}%
289     \ifDTMshowzone
290       \DTMbulgariantimezonesep
291       \DTMdisplayzone{##8}{##9}%
292     \fi
293   }%
294   \renewcommand*{\DTMDisplay}{\DTMdisplay}%
295 }

```

`\DTMbulgarianzonemaps` The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

296 \newcommand*{\DTMbulgarianzonemaps}{%
297   \DTMdefzonemap{02}{00}{EET}%
298   \DTMdefzonemap{03}{00}{EEST}%
299 }

```

Switch style according to the `useregional` setting.

```

300 \DTMifcaseregional
301 {}% do nothing
302 {\DTMsetstyle{bulgarian}}
303 {\DTMsetstyle{bulgarian-numeric}}

```

Redefine `\datebulgarian` (or `\date<dialect>`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

304 \ifcsundef{date\CurrentTrackedDialect}
305 {%
306   \ifundef\datebulgarian
307   {% do nothing
308   }%

```

```
309  {%
310    \def\datebulgarian{%
311      \DTMifcaseregional
312      {}% do nothing
313      {\DTMsetstyle{bulgarian}}%
314      {\DTMsetstyle{bulgarian-numeric}}%
315    }%
316  }%
317 }%
318 {%
319   \csdef{date\CurrentTrackedDialect}{%
320     \DTMifcaseregional
321     {}% do nothing
322     {\DTMsetstyle{bulgarian}}%
323     {\DTMsetstyle{bulgarian-numeric}}%
324   }%
325 }%
```

Change History

1.0		1.1
General: Initial release 1, 3, 5	General: removed spurious space .. 9

Index

D		\DTMbulgarianordinal 2, 3
\DTMbulgariandatesep 6	\DTMbulgariantimesep 6
\DTMbulgariandatetimesep 6	\DTMbulgariantimezonesep 6
\DTMbulgariandaymonthsep 6	\DTMbulgarianyear 2, 3
\DTMbulgarianMonthname 2, 4	\DTMbulgarianzonemaps 9
\DTMbulgarianmonthname 2, 4	U	
\DTMbulgarianmonthyearsep 6	useregional 1, 9